

# BIOTHANE PRODUCT NUMBER CHART

B10 SH 100 BL 520 - OLEM - T078B						
WEBBING*		PROFILE	WIDTH	COLOR	COATING	ROLL SIZE & EMBOSS
<b>B05</b> 400 lbs 181 kg		<b>UT</b> ultra thin .035"/.89mm	<b>038</b> 3/8"/10mm	<b>BL</b> black	<b>100<sup>s</sup></b> Gold Opaque	<b>0050</b> 50'/15m roll no emboss
		<b>TF</b> thin flex .050"/1.3mm	<b>012</b> 1/2"/13mm	<b>BR</b> brown		
<b>B07</b> 600 lbs 272 kg		<b>UF</b> ultra flex .055"/1.4mm	<b>058</b> 5/8"/16mm	<b>BU</b> blue	<b>300<sup>s</sup></b> Gold Translucent	<b>0100</b> 100'/30m roll no emboss
				<b>CB</b> coyote brown		
<b>B10</b> 1000 lbs 454 kg		<b>SF</b> super flex .060"/1.5mm	<b>034</b> 3/4"/19mm	<b>CL</b> clear	<b>230<sup>s</sup></b> Granite®	<b>0200</b> 200'/61m roll no emboss
		<b>HF</b> high flex .080"/2.0mm	<b>078</b> 7/8"/22mm	<b>DT</b> desert tan	<b>280<sup>s</sup></b> Diamond	
<b>B15</b> 1200 lbs 544 kg		<b>AD</b> adjustable .090"/2.3mm	<b>100</b> 1"/25mm	<b>FG</b> foliage green		<b>OSEM</b> various sand emboss
				<b>GN</b> green	<b>400<sup>s</sup></b> Griamond®	
<b>B20</b> 1500 lbs 680 kg		<b>ST</b> standard* .100"/2.5mm	<b>118</b> 1 1/8"/29mm	<b>GY</b> grey		<b>OLEM</b> various leather emboss
		*GROOVED AVAILABLE <b>G2/G3/G4</b>	<b>114</b> 1 1/4"/32mm	<b>OD</b> olive drab	<b>520<sup>s</sup></b> Beta®	
<b>B30</b> 3000 lbs 1361 kg		<b>SB</b> beaded .160"/4.1mm	<b>112</b> 1 1/2"/38mm	<b>OR</b> orange		
		<b>X2</b> extra thick grooved .130"/3.3mm	<b>134</b> 1 3/4"/44mm	<b>PC</b> pink coral		
		<b>SH</b> super heavy* .150"/3.8mm	<b>200</b> 2"/51mm	<b>PK</b> pink	<b>951</b> Rough Foam	
		*GROOVED AVAILABLE <b>S2</b>	<b>212</b> 2 1/2"/63mm	<b>RD</b> red	<b>961</b> Smooth Foam	
		<b>TK</b> super thick* .185"/4.7mm	<b>300</b> 3"/76mm	<b>SI</b> silver		
		*GROOVED AVAILABLE <b>T2</b>	<b>400</b> 4"/102mm	<b>TE</b> teal		
		<b>QT</b> quarter thick* .250"/6.4mm		<b>TN</b> tan		
		*BUMPS AVAILABLE <b>QT</b>		<b>VI</b> violet		
		<b>CR</b> coated rope .235"/6.0mm (014) .295"/7.5mm (516)		<b>WH</b> white		
		<b>OVAL BELT</b> call for details		<b>WN</b> wine		
				<b>YE</b> yellow		



800.487.2358  
**BIOTHANE.US**

\*WEBBING BREAK STRENGTH  
(LBS) PER INCH OF WIDTH