

SAFETY DATA SHEET

SUPA-STIK ADHESIVE AEROSOL 500ml

SECTION 1; IDENTIFICATION OF THE SUBSTANCES/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name

SUPA-STIK

Product No.

1.2. Relevant identified uses of the substances or mixture and uses advised against

Identified uses Aerosol Spray Adhesive

1.3. Details of the supplier of the data sheet

Supplier Anglo Adhesives & Services Ltd

Anglo House, The Airfield

Dalby Road Melton Mowbray LE13 OBL, UK

1.4. Emergency telephone number

+44 (0) 1664 480866

Mon - Thurs 0830-1700: Fri 0830-1400

SECTION 2; HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (EC 1272/2008) Physical and chemical hazards Extremely Flam. Aerosol - H222

Human health Carc.2 – H351

Skin. Irrit. 2 – H315 Eye Irrit. 2 – H319 STOT SE 3 – H336

Environment Not Classified

The full text for all Hazard statements are displayed in Section 16.

2.2 Label Elements

Contains DICHLOROMETHANE

Label in Accordance with (EC) No. 1272/2008











GHS02	GHS08

Signal word	Danger	
Hazard statements	5	
	H222	Extremely flammable aerosol.
	H351	Suspected of causing cancer
	H315	Causes skin irritation.
	H319	Causes serious eye irritation.
	H229	Pressurized container; may burst if heated
	H336	May cause drowsiness or dizziness
Precautionary Stat	ements	
	P102	Keep out of reach of children
	P210	Keep away from heat/sparks/open flames/hot
		surfaces – No Smoking.
	P251	Pressurized container: Do not pierce or burn, even
		after use.
	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	P281	Use personal protective equipment as required.
	P501	Dispose of contents/container in accordance with
		Local Regulations.

Supplementary precautionary statements

P273	Avoid release to the environment.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P340	IF INHALED: Remove victim to fresh air and keep at
	rest in position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several
	minutes. Remove contact lenses, if present and easy
	to do. Continue Rinsing.
P308+313	If exposed or concerned: Get medical advice/attention
P410+412	Protect from sunlight. Do not expose to temperatures
	Exceeding 50°C/122°F.

Supplement label information

2.3. Other hazards

Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent material – NO SMOKING.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS



3.2 Mixtures

DICHLOROMETHANE 10-40%

CAS-No.: 75-09-2 EC No.: 200-838-9

Classification (EC 1272/2008)

Carc.Cat 2 – H351 Skin Irrit Cat 2 – H315 Eye Irrit Cat 2 – H319 STOT SE Cat 3 – H336

PETROLEUM GASES LIQUIFIED 30-50%

CAS- No.: 68476-85-7 EC No.: 270-704-2

Classification (EC 1272/2008)

Flam. Gas 1- H220

The full text for all R-Phrases and Hazard statements are displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

DO NOT induce vomiting. Get medical attention immediately

Skin contact

Wash the skin immediately with soap and water. Promptly remove clothing if soaked through and wash as above. Get medical attention if any discomfort continues.

Eye Contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling section 2.2, and/or in section 11.

4.3 Indication of any immediate medical attention and special treatment needed

No data available



REV 5.0

DECEMBER 2021

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Extinguishing media

Fire can be extinguished using: foam; carbon dioxide; dry powder

5.2 Special hazards arising from the substance or mixture

Unusual fire & Explosion hazards

Canisters may explode in fire.

Toxic gases/vapours/fumes of: Carbon Dioxide (CO₂). Carbon Monoxide (CO)

5.3 Advice for firefighters

Wear self-contained breathing apparatus.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact. Ensure adequate ventilation. Avoid breathing vapours, mist or gas. Wear personal protective equipment (see section 8).

6.2 Environmental precautions

Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environment Agency or other regulatory body. Do not discharge into drains or watercourses or onto the ground.

6.3 Methods and material for containment and cleaning up

Provide ventilation and confine spill. Do not allow runoff to sewer. Absorb in vermiculite, dry sand or earth, and place into containers.

6.4 Reference to other sections

Wear protective clothing as described in section 8 of this safety data sheet. For waste disposal see section 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Must not be exposed to direct sunlight or temperatures above 50°C.

7.3 Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters



Name	STD	TWA - 8 H	irs	STEL - 15	Min	Notes
DICHLOROMETHANE	WEL	100 ppm(Sk)	353 mg/m3(Sk)	200 ppm (Sk)	706 mg/m3 (Sk)	IRELAND TWA:50ppm TWA:174 mg/m3 STEL:150ppm STEL:552 mg/m3
PETROLEUM GASES LIQUIFIED	WEL	1000 ppm (Sk)	1250 mg/m3(Sk)	1250 ppm(Sk)	2180 mg/m3(Sk)	IRELAND TWA:500ppm TWA:625mg/m3 STEL:625ppm STEL:1090mg/m3

WEL = Workplace exposure limit.

Ingredient comments

8.2 Exposure controls

Protective equipment









Appropriate engineering controls

Observe any occupational exposure limits for the product or ingredients. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist.

Eye/face protection

Chemical splash goggles or face shield. Use equipment for eye protection tested and approved under appropriate government standards such as EN 166(EU).

Hand protection

Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Nitrile rubber.

Other skin and body protection

Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Wear protective clothing.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Use respirators and components tested and approved under appropriate government standards such as CEN (EU).



Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

(a) Appearance Canister/Aerosol.

(b) Odour Chlorinated Hydrocarbon

(c) Odour ThresholdNo data available(d) pHNot applicable(e) Melting point/freezing pointNo data available(f) Initial boiling point and boiling range40°C (approx.)(g) Flash pointEstimated at -35°C(h) Evaporation pointNo data available(i) Flammability (solid gas)No data available

(j) Upper/lower flammability

Or explosive limits

(k) Vapour pressure

(l) Vapour density

(m) Relative density

No data available

No data available

No data available

(n) Water solubility Slightly soluble in water; soluble in chlorinated

hydrocarbons

(o) Partition coefficient

n-octanol/waterNo data available(p) Auto-ignition temperatureNo data available(q) Decomposition temperatureNo data available(r) ViscosityNo data available(s) Explosive propertiesNo data available(t) Oxidising propertiesNo data available

9.2. Other information

Can pressure 70psi.

9.2 Other information

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No data available.

10.2 Chemical stability

Avoid heat, sparks, and flames, stable under normal conditions.

10.3 Possibility of hazardous reactions

No data available.



10.4 Conditions to avoid

Avoid heat, flames and other sources or ignition. Avoid contact with: Strong oxidising agents, Strong alkalis and Strong mineral acids.

10.5 Incompatible materials

Materials to avoid

Strong acids, strong oxidising substances and strong alkalis.

10.6 Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO); Carbon Dioxide (CO2); Phosgene (COCl2); Hydrogen Chloride (HCl). Slow hydrolysis with water forms hydrochloric acid.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute Toxicity

LD50 Oral - Rat - >2,000 mg/kg

Inhalation

LD₅₀ Inhalation – Rat – 52,000 mg/m³

Skin contact

Skin - Rabbit

Result: Irritating to skin - 24 hr

(Draize Test)

Eye contact

Eyes – Rabbit

Result: Irritating to eyes - 24 hr

(Draize Test)

Carcinogenicity

Carcinogenicity – Rat – Inhalation

Tumorigenic: Carcinogenic by RTECS criteria. Endocrine: Tumours

Limited evidence of carcinogenicity in animal studies.

Suspected human carcinogens

IARC: 2B – Group 2B: Possible carcinogenic to humans (Methylene Chloride)

Specific Target Organ Toxicity - Single Exposure

May cause respiratory irritation.

May cause drowsiness or dizziness

Aspiration Hazard

No data available.



SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Not regarded as dangerous to the environment. However, contamination of the aquatic or terrestrial environments should be avoided

12.1 Toxicity

Toxicity to fish LC50 – Pimphales promelas (fathead monnow) – 193.00 mg/l – 96 hr

NOEC – Cyprindon variegatus (sheepshead minnow) – 130 mg/l – 96 hr

Toxicity to daphnia and other

Aquatic invertebrates: EC50 – Daphnia magna (Water f;ea) – 1,682.00 mg/l – 48 hr

12.2 Persistence and degradability

Biodegradability Result <26% - Not readily biodegradable

12.3 Bio accumulative potential

Does not bioaccumulate

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB Assessment

Contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1 UN Number

UN No (ADR/RID/ADN) 1950 UN No (IMDG) 1950 UN NO (ICAO) 1950

14.2 UN Proper Shipping Name

ADR/IMDG/AND/RID AEROSOLS

IATA Aerosols Flammable

14.3 Transport Hazard Class(es)

ADR/RID/ADN Class 2.1

ADR/RID/ADN Class Class 2: Gases ADR Label No 2.1 & 6.1



IATA 2.1 **IMDG Class** 2.1 ICAO Class/Division 2.1 **ICAO Subsidiary Risk** 6.1 **ICAO TEC* No** 20GSF Air Class 2.1 **UK Road Class** 2.1 **Transport Labels** L.Q.



14.4 Packing Group

Not Applicable

14.5 Environmental Hazards

Dangerous for the environment No Marine pollutant No

Other information No supplementary information available

14.6 Special Precautions for user

Overland Transport

Classification Code (ADR): 5F

Special Provisions (ADR): 190,327,344,625

Limited Quantities (ADR): 11
Excepted Quantities (ADR): E0

Packing Instructions (ADR): P207,LP02
Special Packing provisions (ADR): PP87, RR6, L2

Mixed Packing provisions (ADR): MP9
Transport Strategy (ADR): 2
Special provisions for carriage – Packages (ADT) V14

Special Provisions for carriage – Loading, unloading

and handling (ADR): CV9, CV12

Special provisions for carriage – Operation (ADR): S2
Tunnel Restriction Code: D

Transport by Sea

Special Provisions (IMDG): 63,190,277,327,344,959

Limited Quantities (IMDG):

Excepted Quantities (IMDG):

Packing Instructions (IMDG):

Special Packing provisions (IMDG):

EmS-No (Fire):

EmS-No (Spillage):

SP277

Evaluation Special P207,LP02

P207,LP02

PP87,L2

F-D

S-U

Stowage category (IMDG):NoneStowage and Handling (IMDG):SW1,SW22Segregation (IMDG):SG69MFAG-No:126

Air Transport

PCA Excepted Quantities (IATA): E0



PCA Limited Quantities (IATA):

PCA Limited Quantity max net quantity (IATA):

PCA Packing instructions (IATA):

PCA max net quantity (IATA):

CAO packing instructions (IATA):

CAO max net quantity (IATA):

150Kg

Special provisions (IATA): A145,A167,A802

ERG Code (IATA): 10L

Inland Waterway Transport

Classification Code (ADN): 5F

Special Provisions (ADN): 190,327,344,625

Limited Quantities (ADN):

Excepted Quantities (ADN):

Equipment required (ADN):

Ventilation (ADN):

VE01,VE04

Number of blue cones/lights (ADN): 1

Rail Transport

Classification Code (RID): 5F

Special Provisions (RID): 190,327,344,625

Limited Quantities (RID): 1L Excepted Quantities (RID): E0

Packing Instructions (RID): P207,LP02
Special Packing provisions (RID): PP87,RR6,L2

Mixed Packing provisions (RID): MP9
Transport Category (RID): 2
Special Provisions for carriage – Packages (RID): W14

Special Provisions for carriage – Loading, unloading

and handling (RID): CW9, CW12

Colis Express (express parcels) (RID): CE2
Hazard Identification No (RID): 23

14.7 Transport in bulk according to Annex II of MARPOL and the IBC code

Not applicable

Section 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Labelling according to Regulation (EC) No 1272/2008

The chemicals (Hazard information and packaging for supply) regulations 2009 (S.I 2009 No. 716). Control of substances hazardous to health.

Approved code of practice.

Guidance notes

Workplace exposure limits EH40.

15.1.1 EU-Regulations

Contains no REACH substances with Annex XVII restrictions.

Contains no REACH Annex XIV substances.

15.1.2 National Regulations



No additional information available.

SECTION 16: OTHER INFORMATION

General information

This product should be used as directed. For further information consult the product data sheet or contact technical services.

Information sources

This safety data sheet was compiled using current safety information supplied by distributor raw materials.

Revision comments

This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact Anglo Adhesives & Services Ltd.

Hazard statements in full

H220	Extremely flammable gas
H222	Extremely flammable aerosol.
H351	Suspected of causing cancer
H315	Causes skin irritation.
H310	Causes serious eye irritation.
H336	May cause drowsiness or dizziness

Abbreviations

Carc 2	Carcinogen Category 2
Skin Irrit 2	Skin Irritant Category 2
Eye Irritant 2	Eye Irritant Category 2

STOT SE 3 Specific Target Organ Toxicity Single Exposure Category 3

Carc Cat 3 Carcinogen Category 3
Flam Gas 1 Flammable Gas Category 1

ISSUE: REV 5.0

LAST REVISED: DECEMBER 2021

Disclaimers Information contained in this publication or as otherwise supplied to

Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their

own particular purpose. Anglo Adhesives & Services Ltd gives no

warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded

except to the extent that exclusion is prevented by law. Anglo

Adhesives & Services Ltd accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information.

Freedom under Patents, Copyright and Designs cannot be assumed.